

FILE NAME: ITL86069.IES

TEST: ITL86069

MANUFACTURER: STONE LIGHTING LLC

LUMINAIRE CATALOG: WS016OPSNLEDG8

LUMINAIRE: FABRICATED SEMI-SPECULAR METAL WALL MOUNTING BRACKET, FROSTED CYLINDRICAL GLASS DIFFUSER WITH WHITE FINISHED INTERIOR. OPEN TOP. DIFFUSER FROSTED SIDE OUT.

LAMP: ONE 4-PIN SINGLE ENDED TWIN TUBE STYLE LED LAMP WITH INTEGRAL LED DRIVER AND WHITE LIGHT EMITTING DIODES (LEDS), STONE LIGHTING PROPRIETARY LMP2G11L8, VERTICAL BASE-DOWN POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 7.32 WATTS, 0.0619 AMPS

MOUNTING: WALL

DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (120VAC, 60Hz) TO THE LAMP. LAMP INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 20.0 FEET

ABSOLUTE LUMENS: 352

TILT: NONE

